

# CENTRAL UNITS

Model number: **AL-CPU-M.2-A.11i**

## DESCRIPTION:

Ambity Line™ Series Central Unit.

The device has a built-in (internal) 8-channel input/output module AL-IO-A.11i.

8 configurable (universal) channels: AI/DI, working as:

- Current analog inputs: nominal ranges 0-20mA
- Voltage analog inputs: nominal ranges 0-10V, 0-24V
- digital inputs (realized as voltage measurement; this allows to set the threshold and hysteresis): nominal ranges 0-24V

All channels are configurable in the above-mentioned range (each channel can operate as voltage input, current input or digital input).

The device can be extended with external expansion modules, thus increasing the number of inputs/outputs and communication ports.

## SPECIFICATION:

### Power supply:

Voltage	22..24..26 VDC
Power consumption	Typically 150mA @24V (max. 250mA)
Power source	External stabilized power supply
Protection against change of polarity	YES
Internal overload protection	YES (1.5A)
Emergency power supply	YES – external 12V 1.2Ah battery pack Charging with 150mA current via built-in charger

### Processor, memory, performance:

Processor	ARM Cortex-M7 200MHz
User program size	Up to 2 MB Stored in the internal file system
User program memory	1 MB MCU FLASH (fast; program code only) 128 kB MCU SRAM (fast; only stack and program data) 4 MB SDRAM (shared between code and data)
RETAIN data size	0.25 MB (saved to the internal file system when the user program is stopped and restored when the user program is started)
Supported number of inputs/outputs	It results from the modules used. The CPU allows you to connect up to 10 I/O modules, obtaining up to 120 supported I/O (10x external 12-channel module)
Configurable program cycle time	50..1000ms

### Interfaces:

Modbus RTU non-isolated	Operating modes: master, slave Transmission speed: 1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200
Ethernet	10/100 Base-T
Local user interface	OLED display 128x64 pixels, monochrome white 6 buttons
USB-OTG	MicroUSB slot type

	In HOST mode: USB memory support (data transfer from to AL-CPU); supported formats: FAT32 In DEVICE mode: communication with the computer (AL Utility™ program)
microSD	Support for a memory card for data recording and data transfer from/to AL-CPU Supported formats: FAT32
AL-IO-bus	System bus: for communication with AL-IO modules (RS-485 with dedicated communication protocol)

### Measurement and control:

Number of channels including configurable	8 8 (as the signal types listed below)
Signal type	AI/DI (current, voltage or digital)
Galvanic isolation from the system	NO
Galvanic isolation between channels	NO
Measurement speed	min. 10 measurements per second (each channel)
Current inputs:	
ranges of work	0-20mA (max. 0-24mA)
input impedance	~100 Ohms
accuracy	0.15% of the nominal range
temp. stability	0.01%/°C
overcurrent protection	YES
protection against change of polarity	NO (changing the polarity risks damaging the channel)
Voltage inputs:	
ranges of work	0-10V (max. 0-11V) 0-24V (max. 0-28V)
input impedance	~100 kOhm
accuracy	0.15% of the nominal range
temp. stability	0.01%/°C
protection against change of polarity	NO (changing the polarity risks damaging the channel)
Digital input (realized as voltage measurement):	
ranges of work	0-24V
input impedance	~100 kOhm
accuracy	5% of the nominal range
protection against change of polarity	NO (changing the polarity risks damaging the channel)

### ADDITIONAL INFORMATION:

#### Installation:

Type of installation	DIN rail, Type O, 35 mm
Mounting method	Built-in latches (apply-and-press type), no need for additional brackets or adapters
Replacement or expansion	Directly on the DIN rail
Combining modules	Using a bus connector, forming a communication and power bus, installed inside the DIN rail (no wiring required)

#### Housing:

Degree of protection	IP 20/DIN EN 60529
Fabrication material	Polyamide (PA66)
Flammability and fire safety class	UL 94 V0
Color	Light gray RAL 7035 (green plugs)
Dimensions (without plugs)	35 x 99 x 114.5 mm (W x H x D)
Dimensions (with plugs)	35 x 109 x 114.5 mm (W x H x D)

#### Input/output terminals:

Type	Terminal block detachable, screw connectors, single-section
Raster	5.0 mm
Ø hole / cable dimensions	max. power cable cross-section 2.5 mm <sup>2</sup> / max. cable diameter 2.0 mm

Insulation stripping length	7 mm
Screw type	M3

---

**Conditions of use:**

Temp. range	0... +55°C
Humidity	85% max.

---

**Transportation and storage:**

Temp. range	-20... +70°C
Humidity	85% max.
Unit packaging	Cut cardboard box
Number of pieces per package	1
Package dimensions	118 x 80 x 140 mm (W x H x D)
Country of origin	PL

---

**Compliance/certifications:**

CE mark	YES
RoHS rating	YES
REACH Assessment	YES

<http://www.edscontrollers.com/al-cpu-m2-a11i>



**EDS CONTROLLERS®**

brand owner eDev Studio sp. z o.o.  
e-mail [support@edscontrollers.com](mailto:support@edscontrollers.com)  
[www.edscontrollers.com](http://www.edscontrollers.com)